

SJ SERİSİ HİDROLİK DÖNER BAĞLANTI REKORLARI



SJ Serisi Hidrolik Döner Bağlantı Rekorları, hareketli bir hortumda dönmeden kaynaklanan burkulma ve bükülmeyi gidererek zarar görmesini engellemek amacıyla hortumla sabit bir bağlantı parçası arasına monte edilirler.
SJ Serisi Hidrolik Döner Bağlantı Rekorları, hızlı ve sürekli dönüşler için uygun olmayıp, yüksek basınç altındaki yavaş dönüşler için uygundurlar.
SJ Serisinde gövdeler ısıl işlemle sertleştirilmiştir.

Malzeme	Otomat Çeliği
Vida Ölçüsü	BSP (İsteğe Bağlı: NPT, Metrik)
Sızdırmazlık	Nitril O-ring (NBR)
Çalışma Sıcaklığı	-30 °C ile +110 °C
Kaplama	Galvaniz (Chrome III pasivasyon)
Isıl işlem	Gövde
Özel Hallerde	VİTON
Kullanım Alanı	İnşaat, üretim, mobil hidrolik, genel endüstri



SJ SERIES HYDRAULIC SWIVEL JOINTS


SJ Series Hydraulic Swivel Joints are mounted between the end of a moving hose and a fixed component to prevent hose's damaging by compensating its torsion and twisting.
SJ Series Hydraulic Swivel Joints are not suitable for fast and permanent rotations. They are suitable for slow rotations and high pressure applications.
Boddies of SJ Series Hydraulic Swivel Joints are hardened by heat treatment.

Material	Carbon Steel
Thread Size	BSP (Upon Request: NPT, Metric)
Sealing	Nitrile O-ring (NBR)
Working Temperature	-30 °C and +110 °C
Plating	Zinc Plating (Cr III Passivation)
Head Treatment	Body
Upon Reguest	VITON & High temperature resistant special spring (-30 °C & +225 °C)
Applications	Construction, production, mobile hydraulic, general industries











DÜZ TİP DÖNER REKORLAR
INLINE SWIVEL JOINTS



Teknik Özellikler
Technical Specifications

Kod (Code)	Vida Ölçüsü (Thread Size) A	Çalışma Basıncı (Working Pressure) Bar	Ölçüler - mm (Dimensions) - mm				
			B1	B2	L	L1	L2
SJIG14N	1/4" BSP	450	19	30	62	18.70	42
SJIG38N	3/8" BSP	430	24	32	68	22	45
SJIG12N	1/2" BSP	400	27	36	71	23.70	48
SJIG34N	3/4" BSP	380	36	46	81	29.50	50
SJIG1N	1" BSP	340	41	50	90	32.50	57
SJIG114N	11/4" BSP	300	50	60	97	34	63

DİRSEK TİP DÖNER REKORLAR
90° TYPE SWIVEL JOINTS



Teknik Özellikler
Technical Specifications

Kod (Code)	Vida Ölçüsü (Thread Size) A	Çalışma Basıncı (Working Pressure) Bar	Ölçüler - mm (Dimensions) - mm				
			B1	B2	C	D	L
SJ90G14N	1/4" BSP	450	19	32	10.60	47.50	69
SJ90G38N	3/8" BSP	430	24	36	13.30	50	77
SJ90G12N	1/2" BSP	400	27	46	13.80	59	88
SJ90G34N	3/4" BSP	380	36	50	19.30	62.50	101
SJ90G1N	1" BSP	340	41	60	23	69	113
SJ90G114N	11/4" BSP	300	50	67	31.50	67	118