

CVSS SERİSİ AISI 316-L PASLANMAZ ÇEK VALFLER

Komple olarak AISI 316-L kalite paslanmaz çelikten imal edilen CVSS Serisi Çek Valfler, her türlü kimyasala ve korozyona karşı mükemmel dirence sahiptir.
CVSS Serisi Çek Valfler, kısma noktalarının baypasında, akışkanın bir yönde engellenmesinde, tanka tahliye valfi olarak ve devrelerde belirli bir karşı basınç üretilmesi için ön gerilim (tutma) valfi olarak kullanılmaktadır.
CVSS Serisi Paslanmaz Çek Valflerde açma basıncı standart olarak 0,5 Bardır.
Özel olarak 6-8 Bar açma basınçlı paslanmaz çek valfler de stoklarımızda mevcuttur.

Malzeme	AISI 316-L kalite paslanmaz çelik
Vida Ölçüsü	BSP (İsteğe Bağlı: NPT, Metrik)
Sızdırmazlık	VİTON
Açma Basıncı	0,5 Bar (Özel hallerde isteğe bağlı 6-8 Bar açma basıncı opsiyonu)
Çalışma Sıcaklığı	-30 °C ile +110 °C
Özel Hallerde	EPDM (Buhar uygulamalarına özel) 6-8 Bar açma basınçlı yay
Kullanım Alanlı	Denizcilik, gıda, ilaç, medikal, kimya, sulama, kağıt, boya, tekstil, gaz ve havacılık



CVSS SERIES AISI 316-L STAINLESS STEEL CHECK VALVES

CVSS Series Check Valves are completely made of AISI 316-L stainless steel row material have an excellent resistance to all kind of chemical and corrosion.
CVSS Series Check Valves are also used for by-pass of throttle points, for flow prevention in one direction, for discharging valve and for hold valve.
Opening pressure of CVSS Series Hydraulic Check Valves is 0,5 Bar. Upon request, 6-8 Bar opening pressure is optional.


Material	AISI 316-L stainless steel
Thread Size	BSP (Upon Request: NPT, Metric)
Opening Pressure	0,5 Bar (6-8 Bar opening pressure is optional, open request)
Sealing	VITON
Working Temperature	-30 °C and +110 °C
Upon Request	EPDM (For steam application) Special spring for optional 6-8 Bar opening pressure
Applications	Marine, food, pharmacy, medical, chemical, irrigation, paper, paint, textile, gas and aviation




Açma basıncı 6 - 8 Bar olan hidrolik paslanmaz çek valflerimiz de stoklarımızda mevcuttur.

Stainless steel check valves of which cracking pressure is 6 - 8 Bar are also available in stock.







Teknik Özellikler
Technical Specifications

Kod (Code)	Vida Ölçüsü (Thread Size)	Açma Basıncı (Crack Pressure) Bar	Çalışma Basıncı (Working Pressure) Bar	Ölçüler - mm (Dimensions) - mm				
				A	B	C	D	F
CVSSG18V	1/8" BSP	0.5	580	46,50	9	28,50	14,50	15
CVSSG14V	1/4" BSP	0.5	450	55	10	35	18	19
CVSSG38V	3/8" BSP	0.5	450	60	11	38	21	22
CVSSG12V	1/2" BSP	0.5	400	70	12	45	26	27
CVSSG34V	3/4" BSP	0.5	380	83	17	50	35	36
CVSSG1V	1" BSP	0.5	350	98	20	60	40	41
CVSSG114V	11/4" BSP	0.5	350	110	21	68	49	50
CVSSG112V	11/2" BSP	0.5	280	115	22	71	58	60
CVSSG2V	2" BSP	0.5	260	130	25	80	73	75

Debi / Basınç Değişimi Tablosu
Flow Rate / Pressure Drop Table

Kod (Code)	Vida Ölçüsü (Thread Size)	Basınç Değişimi (Pressure Drop) - Δ p		
		1 Bar	2 Bar	5 Bar
CVSSG18V	1/8" BSP	10	14	23
CVSSG14V	1/4" BSP	16	25	36
CVSSG38V	3/8" BSP	25	38	70
CVSSG12V	1/2" BSP	50	70	130
CVSSG34V	3/4" BSP	115	170	320
CVSSG1V	1" BSP	160	255	430
CVSSG114V	11/4" BSP	240	365	650
CVSSG112V	11/2" BSP	340	475	800
CVSSG2V	2" BSP	750	1025	1680

